



The new FCB: Checkweighing and portioning scale with up to three interfaces, with optional verification

Features

- Standardised, convenient KERN concept of operation, consistency across products in terms of design, menu structure, button functions, interface connection and interface protocol
- Compact size
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay. Available as an option: RS-232, USB, Ethernet, WiFi, Bluetooth

- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers. For further information on KUP and KCP see page 18/19
- Thanks to battery operation/rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- Weighing with tolerance range: a visual and audible signal helps with portioning, dispensing or grading
- Summation of weight values
- Protective working cover included with delivery


Technical data

- Backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, WxD 252x225 mm
- Overall dimensions WxDxH 322x267x91 mm
- Net weight approx. 3,8 kg
- Permissible ambient temperature
KERN FCB: 0 °C/40 °C
KERN FCB-M: -10 °C/40 °C

Accessories

- Protective working cover, scope of delivery 5 items, KERN YBA-A14S05,
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01
- Signal lamp for visual support of weighing with tolerance range. connection is only possible in combination with KUP-01 (RS-232 interface), KERN CFS-A03
- External data interface RS-232, interface cable included, KERN KUP-01
- External data interface USB, interface cable included, KERN KUP-03
- Ethernet interface adapter, KERN KUP-04
- WiFi interface adapter, KERN KUP-05
- Bluetooth interface adapter, KERN KUP-06
- Extension box for connecting up to three interfaces in parallel, KERN KUP-13
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION



FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Smallest part weight (Normal) g/piece	Options	
						Verification	DAkkS Calibr. Certificate
KERN						M KERN	DAkkS KERN
FCB 6K-5	6	0,05	-	-	0,5	-	963-128
FCB 8K0.1	8	0,1	-	-	1	-	963-128
FCB 12K-4	12	0,1	-	-	1	-	963-128
FCB 12K1	12	1	-	-	10	-	963-128
FCB 30K-4	30	0,2	-	-	2	-	963-128
FCB 30K1	30	1	-	-	10	-	963-128

Multi-division balance, with increasing or decreasing load, it switches automatically to the next largest or smallest weighing range [Max] and readout [d].

FCB 6K-3DM	NEW	3 6	1 2	1 2	20	2	965-228	963-128
FCB 15K-3DM	NEW	6 15	2 5	2 5	40	5	965-228	963-128
FCB 30K-3DM	NEW	15 30	5 10	5 10	100	10	965-228	963-128

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

NEW New model