

NEW



Discover more details and matching accessories online!

## Entry-level bench scale with stainless steel weighing plate and checkweighing function, with optional verification

Features	Technical data	Main scope of applications
<ul style="list-style-type: none"> <li>• Weighing with tolerance range (checkweighing): a visual signal helps with portioning, dispensing or grading</li> <li>• Stainless steel weighing plate, which makes cleaning easy and hygienic</li> <li>• Integrated piece-counting function with storable piece weight</li> <li>• Sleep function: The scale automatically switches to energy-saving mode after an adjustable period of inactivity</li> </ul>	<ul style="list-style-type: none"> <li>• Large backlit LCD display, digit height 25 mm</li> <li>• Dimensions weighing surface, stainless steel, WxD 190x230 mm</li> <li>• Overall dimensions WxDxH 288x233x102 mm</li> <li>• Net weight approx. 1,8 kg</li> <li>• Permissible ambient temperature -10 °C/40 °C</li> </ul>	<ul style="list-style-type: none"> <li>• Gastronomy</li> <li>• Food production</li> <li>• Agriculture</li> <li>• Agribusiness</li> </ul>

STANDARD      OPTION      FACTORY

FPE-M

Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Smallest part weight (Normal) g/piece	Options	
						Verification	Calibr. Certificate
KERN						M KERN	DAkkS accr. KERN
FPE 3K-4	3	0,2	-	-	2	-	963-127
FPE 6K-3	6	0,5	-	-	5	-	963-128
FPE 15K-3	15	1	-	-	10	-	963-128
FPE 30K-3	30	2	-	-	20	-	963-128

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

FPE 3K-3M	3	1	1	20	10	965-227	963-127
FPE 6K-3M	6	2	2	40	20	965-228	963-128
FPE 15K-3M	15	5	5	100	50	965-228	963-128
FPE 30K-2M	30	10	10	200	100	965-228	963-128